

[Web](#) [Images](#) [Groups](#) [News](#) [Froogle](#) [Maps](#) [more »](#)

mpeg element predicate constant variable add

[Advanced Search](#)
[Preferences](#)**Web** Results 1 - 10 of about 13,900 for [mpeg element predicate constant variable address attributes](#). (0.42)

A Logic Approach for MPEG-7 XML Document Queries

MEMBERP(d tv) where d is a **constant** or **variable**, and tv is an **element address variable** or an **element** with a datatype for asserting logic truth about member ...

www.mulberrytech.com/Extreme/Proceedings/html/2001/Liu01/EML2001Liu01.html - 50k -

[Cached](#) - [Similar pages](#)

[PDF] A Logic Approach for MPEG-7 XML Document Queries

File Format: PDF/Adobe Acrobat - [View as HTML](#)

xn, c, t, a is a **constant** or **variable**. The **predicate** E(x1, x2, ..., xn, c, t, a) stands for a logic assertion that **element "t"** at **address "a"** contains "c" ...

www.mulberrytech.com/Extreme/Proceedings/xslfo-pdf/2001/Liu01/EML2001Liu01.pdf -

[Similar pages](#)

[[More results from www.mulberrytech.com](#)]

A Logic Approach to XML Document Update Query Specifications

E(x1, x2, ..., xn, c, t, a), where E is an **element predicate** and each of x1, x2, ..., xn, c, t, a is a **constant** or **variable**. The **predicate** E(x1, x2, ...

www.gca.org/papers/xmleurope2001/papers/html/s13-2.html - 41k - [Cached](#) - [Similar pages](#)

[PDF] A predicate logic approach for MPEG-7 XML document queries

File Format: PDF/Adobe Acrobat

variables including tag, **attribute**, content, **address**, and datatype, ... TYPEP(x tn) where x is a **constant** or **variable** and tn is an **element datatype** ...

www.ingentaconnect.com/content/mitpress/mlang/2001/00000003/00000003/art00009 -

[Similar pages](#)

[PDF] Path Predicate Calculus: Towards a Logic Formalism for Multimedia ...

File Format: PDF/Adobe Acrobat

is a **constant** or **variable**. The **predicate** E(x1, x2, ..., xn, c, t, a) stands for a logic assertion that **element "t"** at **address "a"** ...

www.ingentaconnect.com/content/mitpress/mlang/2001/00000003/00000001/art00010 -

[Similar pages](#)

MPEG-7 Overview

Removal of an **address**, from the point of view of the application, via the current description tree, removes only the content (sub-**elements** and **attributes**), ...

www.chiariglione.org/mpeg/standards/mpeg-7/mpeg-7.htm - 307k - [Cached](#) - [Similar pages](#)

./ Man Openwin_html/html3/toc.html

... XCheckIfEvent, XPeekIfEvent - check the event queue with a **predicate** procedure ...

tt_message_address - retrieve the **address attribute** from a message ...

www.cs.rit.edu/~hpb/Man/_Man_Openwin_html/html3/toc.html - 94k -

[Cached](#) - [Similar pages](#)

[PDF] A Unified Data Model for Representing Multimedia, Timeline, and ...

File Format: PDF/Adobe Acrobat - [View as HTML](#)

The **attributes** of a multimedia entity are frequently read- ... ranges, particularly when a stream **element predicate** holds ...

www.mmss.cs.ucla.edu/k0746.pdf - [Similar pages](#)

[PDF] A Logic Based Approach for the Multimedia Data Representation and ...

File Format: PDF/Adobe Acrobat

to the raw data segment (using the **MPEG-7 MediaLocator element**). Therefore, the

<http://www.google.com/search?sourceid=navclient&ie=UTF-8&rls=GGLD,GGLD:2004-3...> 7/27/2006